



Material (film): 100um

Upper material: opak-matt, monomer plasticized PVC-film (calendered)

Durability: up to 5 years (black & white) / up to 3 years (color)

Films with test flame retardant (DIN EN 13501-1)

Art.-Nr.			Art.-Nr.		
11532	ca. RAL 1015 Hellelfenbein Light Ivory		11550	ca. RAL 5012 Prozessblau Process Blue	
11560	ca. RAL 1018 Gelb Yellow		11503	ca. RAL 5017 Blau Blue	
11504	ca. RAL 1021 Rapsgelb Canola Yellow		11571	ca. RAL 5005 Signalblau Signal Blue	
11544	ca. RAL 1003 Signalgelb Signal yellow		11572	RAL 5002 Reflexblau Reflex Blue	
11528	ca. RAL 2003 Pastellorange Pastel Orange		11573	ca. RAL 5002 Ultramarinblau Ultramarine Blue	
11501	ca. RAL 3020 Verkehrsrot Traffic Red		11512	ca. RAL 5003 Saphirblau Sapphire Blue	
11562	ca. RAL 3001 Signalrot Signal Red		11516	ca. RAL 9010 Weiß White	
11551	ca. RAL 3002 Karminrot Carmine Red		11549	ca. RAL 7035 Lichtgrau Light Grey	
11510	ca. RAL 3000 Feuerrot Soft Red		11509	ca. RAL 7042 Verkehrsgrau Traffic Grey	
11526	Gelbgrün Yellow Green		11519	ca. RAL 7012 Basaltgrau Basalt Grey	
11506	ca. HKS 66 Hellgrün Light Green		11515	RAL 9005 Schwarz Black	
11536	ca. RAL 6029 Laubgrün Forest Green				